Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L4	39	current near sensor near stator	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/09/15 09:42
L5	1	current near sensor near stator and hall	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	ÖR	OFF	2005/09/15 09:42
L6	15	("3329869" "3358208" "3404313" "4041541" "4379291" "4733117" "5003208" "5571568" "5798591" "5925952" "5939813" "5998894").PN.	US-PGPUB; USPAT; USOCR	OR	OFF	2005/09/15 09:44
L7	3.	6 and hall	US-PGPUB; USPAT; USOCR	OR	OFF	2005/09/15 09:48
L8	97	(current near sensor) same stator and hall	US-PGPUB; USPAT; USOCR	OR	OFF	2005/09/15 09:49
S1	0	"10/821,015"	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/09/14 10:14
S2	237	396/508.ccls.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/09/14 11:21
S3	153	"asia optical co"	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/09/14 11:24
S4	4	"asia optical co" and (diaphragm aperture)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/09/14 11:24
S5	6	("4633357" "4842387" "5241251" "5850277" "6510282" "6710563").PN.	US-PGPUB; USPAT; USOCR	OR	OFF	2005/09/15 09:44

S6	2	S5 and sensor	US-PGPUB; USPAT; USOCR	OR	OFF	2005/09/14 15:41
S7	. 68	"current sensor" same inside same motor	US-PGPUB; USPAT; USOCR	OR	OFF	2005/09/14 15:58
S8	1276	"current sensor" same in same motor	US-PGPUB; USPAT; USOCR	OR .	OFF	2005/09/14 15:58
S9	29	"current sensor" same in same motor and camera	US-PGPUB; USPAT; USOCR	OR	OFF	2005/09/14 16:03
S10	1325	(current near sensor) same in same motor	US-PGPUB; USPAT; USOCR	OR	OFF	2005/09/14 16:19
S11	42	(current near sensor) same in same motor and "hall sensor"	US-PGPUB; USPAT; USOCR	OR	OFF	2005/09/14 16:20
S12	14	"hall sensor" near "current sensor"	US-PGPUB; USPAT; USOCR	OR	OFF	2005/09/14 16:29
S13 -	51	"hall sensor" near current	US-PGPUB; USPAT; USOCR	OR	OFF	2005/09/14 16:29